



EonStor GS Gen2 Series

*Enterprise-Class Unified Storage
Integrating SAN, NAS and Cloud*



Highlight

- Consolidates SAN, NAS and Cloud in a single system to enjoy powerful storage features
- Automatically reconnected I/O during path failure
- Cache protection with super-capacitor and flash to ensure data safety
- IDR support ensures that all hard drives are healthy to prevent from rebuilding
- EonOne management interface provides a single control center for system management and resources monitoring

Introduction

The EonStor GS series forms the backbone of our high-performance enterprise storage solution with its powerful performance, flexibility, and high expandability helping to efficiently boost overall productivity. GS can handle large amounts of I/O and file transfers even under high workloads and are especially suitable for hybrid environments adopting SAN, NAS, and Cloud integration. It is perfect for those who want performance, capacity, and a high port count, and at the same time, it is ideal for budget-conscious applications as it can easily meet all general storage needs.

Symmetric active-active controllers

The EonStor GS Series supports symmetric active-active controller configuration for block-level data access to achieve little or no failover time in the event of a path failure.

This design is also able to minimize administrative efforts and boost operation efficiency. Hosts can access the same LUNs simultaneously via both controllers. I/O workloads are more evenly distributed across both controllers and all paths, effectively minimizing costly path management time.

Infinite Storage Capacity on Cloud

The key benefits of cloud storage solutions are their high service durability and the “scale on demand” flexibility allowing to expand storage as your business evolves. As a great on-premises cache/backup storage to cloud storage, EonCloud Gateway features both a wide range integration for both private cloud and public cloud solutions and smart data services such as heterogeneous cache modes, tiering and backup modes to automatically streamline the optimal data flow between local and cloud storage and also save costs.

Comprehensive Data Protection and Security

Security threats are not the only concern when it comes to safeguarding data. Unexpected disk failures, natural disasters, and power outages - all add up to the risk of data loss. EonStor GS series ensures that risk is minimal with its integrated backup functions such as Intelligent Drive Recovery (IDR), snapshot, local replication, remote replication, and file-level rsync.

PHYSICAL SPECIFICATIONS

Product Series		GS 1000 Gen2	GS 3000 Gen2	GS 4000 Gen2
Form Factor	2U 12-bay	GS 1012R2/S2	GS 3012R2/S2	GS 4012R2/S2
	2U 24-bay	GS 1024R2B/S2B	-	-
	2U 25-bay	-	GS 3025R2B/S2B	GS 4025R2B/S2B
	3U 16-bay	GS 1016R2/S2	GS 3016R2/S2	GS 4016R2/S2
	4U 24-bay	GS 1024R2/S2	GS 3024R2/S2	GS 4024R2/S2
	4U 60-bay	-	GS 3060R2L/G2L	GS 4060R2L/G2L
Note: T : High performance G : Single controller S : Single controller(upgradable to dual controller) R : Redundant controller L : One drawer B : 2.5" Form factor 2 : Gen2				
Controller	Dual-redundant or Single upgradable to redundant			
Cache Backup Techniques	Super capacitor+ Flash module (Only for upgradable single controller and dual controller models)			
CPU	Intel® Atom® 4 Core	Intel® Xeon® D 4 Core		Intel® Xeon® D 8 Core
Cache Memory	Default DDR3 16GB Expandable up to 32GB			Default DDR4 16GB Expandable up to 512GB
Supported Drives	2.5" SAS or SATA SSD 2.5" 12Gb/s SAS 10,000 or 15,000 RPM HDD 3.5" 12Gb/s SAS 7,200 RPM HDD 3.5" 6Gb/s SATA 7,200 RPM HDD			
Note: For the latest compatibility details, refer to our official website for the latest Compatibility Matrix.				
Max. Drives Number (via expansion enclosure)	448	896	896	
Max. SSD Cache Pool	1TB	4TB	4TB	
Onboard SAS Expansion Ports	2	4	4	
Onboard 1GbE Ports	8	0	0	
Onboard 10 GbE Ports (SFP+)	0	8	8	
Max. Host Board Slots	2	4	4	
Max. Expansion Board	0	2	2	
Note: The expansion board can only be installed in the HB2 slot and has 12Gb/s SAS x 2 ports only connectable with expansion enclosures.				
Host Board Options	16Gb/s FC x 4 32Gb/s FC x 2 1GbE (RJ-45) x 4 10GbE (SFP+) x 2 10GbE (RJ-45) x 2 25GbE (SFP28) x 2 40GbE (QSFP+) x 2 12Gb/s SAS x 2	16Gb/s FC x 4 32Gb/s FC x 2 32Gb/s FC x 4 10GbE (SFP+) x 2 10GbE (RJ-45) x 2 25GbE (SFP28) x 2 12Gb/s SAS x 2		
Note: 1. The two controllers must have identical slot settings. 2. Fibre channel supports point-to-point and switch mode.				
Max. 16Gb/s FC Ports	8	16	16	
Max. 32Gb/s FC Ports	4	16	16	
Max. 1 GbE Ports	16	0	0	
Max. 10GbE Ports (RJ-45)	4	8	8	
Max. 10GbE Ports (SFP+)	4	16	16	
Max. 25GbE Ports (SFP28)	4	8	8	
Max. 40GbE Ports (QSFP+)	4	0	0	
Max. 12Gb/s SAS Ports	6	12	12	
Expansion Enclosure (JBOD)	JB 3012A, JB 3016A, JB 3024BA, JB 3025BA, JB 3060L	JB 3012A, JB 3016A, JB 3025BA, JB 3060L		
Dimensions (without chassis ears/ protrusions) (W x H x D)	2U 12-bay: 449 x 88 x 500 mm 2U 24-bay: 449 x 88 x 500 mm 2U 25-bay: 449 x 88 x 500 mm	3U 16-bay: 449 x 130 x 500 mm 4U 24-bay: 448 x 174.4 x 500 mm 4U 60-bay: 447.6 x 176 x 840.9 mm		
Package Dimensions (W x H x D)	2U 12-bay: 780 x 379 x 588 mm 2U 24-bay: 780 x 338 x 588 mm 2U 25-bay: 780 x 340 x 588 mm	3U 16-bay: 780 x 423 x 588 mm 4U 24-bay: 780 x 465 x 588 mm 4U 60-bay: 620 x 460 x 1140 mm		
Power Supply Unit (with fan module)	Power Supplies (Redundant/hot-swappable)	460W x 2 (80 PLUS Bronze)	GS 3000/4000: 530W x2 (80 PLUS Bronze) GS 3060L/4060L: 1200W x 2 (80 PLUS Platinum)	
	AC Voltage (with PFC(auto-switching))	100VAC @8A to 240VAC @4A	GS 3000/4000: 100VAC @10A to 240VAC @5A GS 3060L/4060L: 100-127VAC @12.47A, 200-240VAC @7.08A	
	Frequency	50-60 Hz	47-63Hz	
Note: Power is also supplied in redundant mode, allowing full operation with half the resources.				
Safety Standard	<ul style="list-style-type: none"> Electromagnetic Compatibility : CE, BSMI, FCC Safety : UL, BSMI, CB 			

SOFTWARE SPECIFICATIONS

Max. Logical Drives Number	32		
Max. Logical Drives Capacity	512 TB		
Configurable Stripe Size	16KB, 32KB, 64KB, 128KB, 256KB, 512KB, or 1024KB per logical drive		
Configurable Writes Policy	Write-Back or Write-Through per logical drive. This policy can be modified.		
Max. Pool Size	2PB		
Max. Pool Number	32		
Max. Volume Size	2PB		
Max. Volume Number (per pool/per system)	1024		
Max. Host LUN Mapping Number	4096		
Max. Reserved Tag Number per Host-LUN Connection	Up to 256		
Max. iSCSI Initiators (per controller)	832		
Max. Host Connection Number (per FC)	128		
RAID Options	RAID 0, RAID 1, RAID 3, RAID 5, RAID 6, RAID 10, RAID 30, RAID 50, RAID 60		
Protocol Support	File Level Protocol	CIFS/SMB (Version 2.0/3.0), NFS (Version 2/3/4), AFP (Version 2.2.2), FTP/FXP (vsftpd 2.3.4), WebDAV (httpd package 2.4.6)	
	Block Level Protocol	FC, iSCSI, SAS	
	Object Level Protocol	RESTful API	
File Level	Max. File System Size	2PB	
	Max. Number of User Accounts	20000	
	Max. Number of User Groups	512	
	Max. Number of Folder Sharing	2048 (NFS/CIFS/FTP) 255 (AFP)	
	Max. Number of Rsync Jobs	1024	
	Max. Number of Rsync Concurrent Processes	64	
	Max. Number of Concurrent Connections (NFS/CIFS/AFP/FTP)	<ul style="list-style-type: none"> • 16 GB memory: 200 • 32 GB memory: 512 • 64 GB memory: 1024 • 128 GB memory: 2048 	
Management	<ul style="list-style-type: none"> • User account management • Group management • Folder management - folder access control • Quota management 	<ul style="list-style-type: none"> • Integration with Microsoft Active Directory (AD) and LDAP • Folder encryption with AES • Web-based EonOne management software • Storage Resource Management to analyze history records of resource usage 	
Availability and Reliability	<ul style="list-style-type: none"> • Redundant, hot-swappable hardware modules • Device mapper support • Antivirus • Trunk group support 	<ul style="list-style-type: none"> • Cache Safe technology • UPS • WORM (For file level only) • SMB Multichannel 	
Notification	Email, SNMP traps		
Applications	<ul style="list-style-type: none"> • File explorer • Proxy server 	<ul style="list-style-type: none"> • Syslog server • VPN server 	<ul style="list-style-type: none"> • LDAP serve • Docker
Cloud Feature	EonCloud Gateway supports the integration with following cloud providers: Amazon S3, Microsoft Azure, Alibaba Cloud, OpenStack, Baidu Cloud, Google Cloud, Tencent Cloud, Wasabi Cloud, etc. For complete information about cloud provides support, please refer to EonCloud Gateway webpage		
OS Support	Microsoft Windows Server 2019/2016/2012R2/2012/2008R2/2008, Windows 7 SP1, Windows 8.1, Microsoft Windows Hyper-V, Red Hat Enterprise Linux, SUSE Linux Enterprise, Sun Solaris, Mac OS X, VMware, Citrix XenServer, OpenStack Cinder		
	Note: For OS version support, please refer to the compatibility matrix		

DATA SERVICE

Self-encrypting Drives	Unique factory encryption secures data plus makes deletion simple and complete	
Thin Provisioning (Block-Level) (default included)	"Just-in-time" capacity allocation optimizes storage utilization and eliminates allocated but unused storage space	
Local Replication	Snapshot	Snapshot images per source volume Standard License: 64 / Advanced License: 256
		Snapshot images per pool Standard License: 128 / Advanced License: 4096
	Volume Copy/Mirror	Replication pairs per source volume Standard License: 4 / Advanced License: 8
		Replication pairs per system Standard License: 16 / Advanced License: 256
Note: Standard license is included by default and advanced is an optional license		
Remote Replication (Block level)(optional)	Replication pairs per source volume: 8	
	Replication pairs per system: 64	
	Note: 1. The maximum number of replication pair per source volume is up to 8, regardless of remote asynchronous/remote synchronous/local volume pairs 2. 4 x 16Gb FC and 2/4 x 32Gb FC host boards do not support Remote Replication	
Remote Replication(File Level)	Support Rsync with 128-bit SSH encryption	
Automated Storage Tiering(optional)	2 or 4 storage tiers based on drive types	
	SSD supports	
	Automated data migration with scheduling options	
SSD Cache(optional)	Accelerating data access for random read-intensive environments, such as OLTP	
	Supports up to four SSDs per controller	
	Recommended DIMM capacity for SSD Cache pool for GS 1000 Gen2	
	DRAM:8GB	Max SSD Cache Pool Size: 400GB
	DRAM:16GB	Max SSD Cache Pool Size: 600GB
	DRAM:32GB	Max SSD Cache Pool Size: 1,000GB
	Recommended DIMM capacity for SSD Cache pool for GS 3000/4000 Gen2	
	DRAM:8GB	Max SSD Cache Pool Size: 500GB
	DRAM:16GB	Max SSD Cache Pool Size: 1,000GB
	DRAM:32GB	Max SSD Cache Pool Size: 2,000GB
DRAM:64GB and up	Max SSD Cache Pool Size: 4,000GB	

WARRANTY AND SERVICE

Service and Support	Standard Service	3-year limited hardware warranty and 8x5 phone, web, and email support (batteries are covered under warranty for 2 years)
	Upgrade or Extension Options	<p>Warranty extension: Can extended standard service up to 5 years The following Service can be upgraded to 5 years</p> <ul style="list-style-type: none"> • Upgrade: Replacement part dispatch on the next business day • Advanced service: 24x7 phone, web, and email support + onsite diagnostics on the next business day • Premium service: 24x7 phone, web, and email support + onsite diagnostics in 4 hours <p>Note: Options may vary by region. For more details, please contact our sales representatives.</p>
	Infotrend Technical Support	FAQ, Download Center, Licensing Service, Service Request

Asia Pacific (Taipei, Taiwan)
Infotrend Technology, Inc.
Tel : +886-2-2226-0126
E-mail : sales.ap@infotrend.com

China (Beijing, China)
Infotrend Technology, Ltd.
Tel : +86-10-6310-6168
E-mail : sales.cn@infotrend.com

Japan (Tokyo, Japan)
Infotrend Japan, Inc.
Tel : +81-3-5730-6551
E-mail : sales.jp@infotrend.com

Americas (Sunnyvale, CA, USA)
Infotrend Corporation
Tel : +1-408-988-5088
E-mail : sales.us@infotrend.com

EMEA (Basingstoke, UK)
Infotrend Europe Ltd.
Tel : +44(0)-1256-305-220
E-mail : sales.eu@infotrend.com

