
CONDENSER MICROPHONE



Features

- 3.5mm connector for IP cameras with Line IN.
- Omnidirectional condenser microphone that covers a wide angle when recording.
- -40dB high sensitivity for clear sound.
- 5m shielded cable that reduces signal interference.



Specifications

Model	MIC02
S / N Ratio	More than 58dB
Impedance	Low (2.2K ohm Max.)
Directional	Omnidirectional
Microphone Type	Electret Condenser Microphone
Sensitivity	-40±4dB(Omni) At 2.0 V, 2.2K Ohm, 0dB=1V/Pa 1KHz
Microphone Diameter	Ø9.7 × 6.7mm
Max. Operation Voltage	6 V
Standard Operation Voltage	2.0 V
Frequency	100 - 10KHz
Current consumption	0.5mA (Max.)
Wire Spec.	Connect : Ø 3.5mm straight plug
Wire Spec.	Wire : Ø 2.1mm PVC
Wire Spec.	Wire Breaking Strength □ Breaking shall not less than 5KGs
Wire Spec.	Total Resistance : Shall not exceed 0.3ohm per meter
Operating temperature	-20°C - 80°C
Dimensions	Body : 15.5mm×25mm×19mm Wire : 5M±5%
Weight	50g

