

Access Control System Server



Specifications

Model	NAC2064 (Limited stock)
Number of door	Support 64 doors by default, possible to buy door access by multiple of 8, maximum of doors supported 65536
Number of time slot	255
Number of Time zone	33
Number of holiday slot	100
Card capacity	2000
Number of department	100
Network video support	LILIN IP Camera direct or via NAVIGATOR software
Number of IPC/NAV	192



Max. Client Connections	10
Max. Access Controllers	125
Live Channel Max	2
Service mode	Yes
Web Console	Yes
eMail	Yes
Languages	Traditional Chinese, English
Authentication management	Support
User accounts	Max. 1000
Group	Max. 1000
User configuration import & export	Yes
Number of eMap	Max. 50
3D eMap	Yes
eMap Door Control	Yes
eMap Live Video	1 door for up to 3 cameras
eMap Alarm Video Popup	1 door for up to 3 cameras
ANPR trigger (optional)	support trigger IOBOX & NAV Advance DO
Event Search	Event / card / name / door / date
Event Snap	Yes
Event Export	CSV
Event Playback	Support by NAV
Event Video Download	Support by NAV
OS	Windows 10 embedded LTSB
CPU	Intel® Celeron® J4005
Display Card	Intel® UHD Graphics 600
RAM	4GB DDR4
SSD HDD	1 × 128GB M.2 2280 SSD (OS) 1 × 1TB 2.5" SATA HDD (recording)
Time Attendance (ACCTIME)	Included
Facial Recognition Integration (ACCFACE)	Included
Number Plate Integration (ACCANPR)	Included

Acc Control App (ACCAPP)	Included
Additional 8 doors management (ACC 8 DOORS)	Optional

